

PNEUMAX**UE/UK DECLARATION OF CONFORMITY
DICHIARAZIONE UE/UK DI CONFORMITA'**

TX210001/DC

DQ04/03

Pneumax S.p.A.

Via Cascina Barbellina, 10

24050 Lurano (BG) – Italy

Declares under its own responsibility that the product:

*Dichiara sotto la propria responsabilità che il prodotto:***ISO 15552 ECOPLUS-T cylinders
Cilindri ISO 15552 serie ECOPLUS-T****X1386, X1387, X1388 and 1386, 1387, 1388**


to which this declaration relates is in conformity with the following directives and standards or other normative document(s): *al quale questa dichiarazione si riferisce, è conforme alle seguenti direttive e norme o altri documenti normativi:*

2014/34/UE – ATEX	Equipment and protective systems intended for use in potentially explosive atmospheres.
U.K. Regulation SI 2016 No. 1107 (as amended)	The Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016 (as amended)
EN ISO 80079-36:2016	Explosive atmospheres - Part 36: Non-electrical equipment for explosive atmospheres — Basic method and requirements
EN ISO 80079-37:2016	Explosive atmospheres - Part 37: Non-electrical equipment for explosive atmospheres - Non-electrical type of protection constructional safety "c", control of ignition sources "b", liquid immersion "k"

The products bear the following markings:

I prodotti sono marcati con i seguenti contrassegni:

NBR seals version: Basic, Push/pull, aluminum piston, tandem versions Versioni guarniz. NBR: base, stelo passante, pistone alluminio e tandem Code 138_(6,7,8).Ø.stroke.0_(1,2) and X138_(6,7,8).Ø.stroke.0_(1,2) Code 138_(6,7,8).Ø.stroke._K and X138_(6,7,8).Ø.stroke._K Code 138_(6,7,8).Ø.stroke._G and X138_(6,7,8).Ø.stroke._G Code 138_(6,7,8).Ø.stroke.stroke1_(F, D, E) and X138_(6,7,8).Ø.stroke.stroke1_(F, D, E)	   II 3G Ex h IIC T6...T4 Gb X II 3D Ex h IIIC T85°C..T120°C Db X -5°C≤Ta≤35°C (T6/T85°C) -5°C≤Ta≤50°C (T5/T100°C) -5°C≤Ta≤70°C (T4/T120°C)
PUR seals version Versione guarnizioni PUR Code 138_(6,7,8).Ø.stroke.0_(1,2)P and X138_(6,7,8).Ø.stroke.0_(1,2)P PUR seals version + aluminum piston Versione guarnizioni PUR + pistone alluminio Code 138_(6,7,8).Ø.stroke.0_(1,2)PK and X138_(6,7,8).Ø.stroke.0_(1,2)PK	   II 3G Ex h IIC T4...T4 Gb X II 3D Ex h IIIC T130°C Db X -30°C≤Ta≤80°C (T4/T130°C)

Technical File *Fascicolo tecnico* TX210001/DTPPNEUMAX S.p.A.
Lurano (BG) Italy – 05/2023The Legal Representative
Il Legale Rappresentante

Rossella Bottacini